

# BROADCAST TELEVISION AND SATELLITE SIGNAL SWITCHING SYSTEM AND METHOD FOR TELEPHONY SIGNAL INSERTION

## Cross Reference To Related Applications

This application incorporates by reference and claims priority to application Serial Number 60/268,629 filed February 14, 2001 for SATELLITE SIGNAL RECEIVING SYSTEM AND METHOD FOR DIAL TONE INSERTION, and Application  
5 Serial Number 60/344,968 filed December 21, 2001 for SATELLITE SIGNAL DILA TONE INSERTION DEVICE AND METHOD, all commonly owned with the present invention.

## Field of the Invention

The present invention relates generally to electronic signal coupling of multiple signals onto a coaxial cable transport, and in particular to a system and method for providing telephony interfacing to a broadcast television and satellite systems.

## Background of the Invention

Typically, installers of satellite dishes and receivers connect three different signals to the satellite receiver in order for a cable television system to work properly. A connection is made from the antenna, generally a satellite dish, to the receiver. A second connection to the receiver may then include an off air antenna or cable signal so that the receiver can access local television (TV) signals should the  
20 consumer/customer wish to view local TV stations. Thirdly, the installer must provide for a telephone signal (herein referred to as dial tone) connection for use by the customer and the satellite provider.

The service provider typically wants to access the satellite receiver for verifying the location of the receiver. It is of value to the provider to know when a customer is  
25 changing locations of the receiver. Also, if multiple receivers are being used, it is desirable for all receivers using a common satellite dish, dishes, antenna, or antennas to be operable with the same phone line. Telephone connection verification is useful in

preventing piracy of the satellite signal. Satellite providers also use the telephone connection to down load any pay-per-view or other purchases made during a billing period.

Currently, installers use a device often referred to as a multiswitch for combining a satellite signals and an off-air antenna or cable television signal. This new combined signal is then sent out through the output connector of the multiswitch to various coaxial cable (coax) connections located throughout a house or structure, by way of example. Where the coax exits at an interior wall of the house, the installer typically attaches a device called a device called a diplexer that serves to separate the combined signals back out based on frequency bands so they can be connected to the Satellite receiver at their respective input port locations.

The third and last signal, as above described, is as important as the first two signals. Yet it is typically not combined with the first two signals. As a result, the installer must go through a time consuming and often difficult process to provide the dial tone signal. In many situations currently known in the art, a telephone outlet is not conveniently located near preferred television or audio/visual system locations. The installer may choose from available solutions, herein described by way of example to include: "running" new wire to each location of a satellite receiver, a normally difficult and labor intensive procedure; accessing a telephone outlet that is closest to the receiver and running a line within the house, also a labor intensive procedure typically requiring the installer to hide the wire so that it is not exposed for view as it runs across a finished room within the house; and as another option, using wireless phone jacks. However, as is well known in the art, "wireless" is a misnomer in that typical devices require electrical wiring to be run in a home to transmit the phone signal. Further, there are problems associated with the use of wireless phone jacks. In many instances there is too much electrical interference within the setup. An installer must move the base jack to several different electrical outlets in order to minimize interference. Also, if there is an electrical surge, the phone jacks are prone to problems that require the installer to make a service visit in order to get the phone signal reconnected to the satellite receiver. Such methods for providing a dial tone to the satellite receiver is costly from both the labor

and materials points of view and typically add significant cost to the overall system installation.

Signal coupling devices and methods for combining CATV and telephone signals are suggested in the art. By way of example, U.S. Patent No. 5,027,426 to Chiocca, Jr. discloses the use of a duplex filter to place telephony and RF signals on a single coaxial cable (coax), but uses the shield of the coax as the needed second conductor. In practice, the shield typically can be unintentionally grounded during installation, causing undesirable telephony signal transmission problems. U.S. Patent No. 6,144,399 to Manchester et al. discloses a passive system for merging a telephone and broadband signals onto one cable, and by way of example teaches that the outer conductor must remain ungrounded to avoid shorting the telephone electrical to earth ground.

Telephony signals are dc coupled onto the inner and outer conductors of the coaxial cable, while the information wire and reference ground of the broadband signal are ac coupled onto the inner and outer conductors of the coaxial cable. The present invention seeks to overcome such problems by avoiding the need to use both the center conductor and the shield for transmitting the telephony signals and employs the use of digital square wave pulses used by microcontrollers located at each end of the single coax to communicate telephony information to each other. U.S. Patent No. 5,896,556 to Moreland et al. uses the modulation and demodulation of the telephony signals to an RF frequency over the coax. Further, the suggested telephony interface is to be connected at only one place in the system, and prior to any splitters on the coax cable. The present invention seeks to reduce costs and minimize components, and as a result discloses transmission of the telephony baseband requiring no modulation.

### **Summary of the Invention**

In view of the foregoing background, it is therefore an object of the present invention to provide for telephony signal transmission such as dial tone (DT) signal insertion into a satellite system. It is further an object of the present invention to provide DT insertion and management of satellite system, cable television, and local antenna signals using a single radio frequency (RF) cable. These and other objects,

features and advantages according to the present invention are provided in a system including a multiswitch and triplexer that ends all of the various "fixes" that the installer must solve or go through. The system comprises a switch for receiving a plurality of radio frequency signals and providing a selected signal output to a coaxial cable in  
5 response to a control signal, a telephony device for receiving a telephony signal, a controller operable with the switch for providing the selected signal output and operable with the telephony device for receiving telephony information and a baseband communications system operable with the controller and the telephony device for modifying the telephony signal as characterized by a control signal for transmitting a  
10 modified telephony signal through a single center conductor wire of the coaxial cable. One preferred embodiment includes a triplexer for connection to the single cable for receiving the modified telephony signal and the selected radio frequency signal, the triplexer further having a controller communicating with the controller through the single conductor wire and an interface device for connection to a receiver. A method aspect of the present invention includes receiving a plurality of radio frequency signals, processing the radio frequency signals for transmitting to a switch, selecting one radio frequency signal from the plurality of radio frequency signals for transmission through a single cable, receiving a telephony signal, modifying the telephony signal as characterized by a digital control signal for transmitting a modified telephony signal  
20 through a single conductor wire of the single cable, receiving the selected radio frequency signal and the modified telephony signal, processing the modified telephony signal for reforming the telephony signal from the modified telephony signal, and transmitting the telephony signal and the selected radio frequency signal to a receiver.

The system of the present invention permits a merging of all three desired  
25 signals, including a satellite signal, off-air antenna or cable television, and a telephone signal. Further, these signals can be distributed to multiple locations so that the satellite receivers can work independently of one another. As a result, an installer can simply connect a satellite signal, an off-air antenna, and a telephone signal, all at one easy location in a single multiswitch device. The installer also has the option of  
30 connecting the telephone signal at the triplexer instead for providing distribution of dial

tone to other triplexers and receivers through the multiswitch in situations where a telephone signal is not present at the multiswitch location. The installer connects the existing cabling to the outputs of the multiswitch device and delivers all three signals over one coax to each receiver location. This triplexer separates out the multiplexed signals so that the installer can connect them to their respective connections on the receiver. This is an easy solution for the installer or the homeowner. A single system that can merge all three signals and distribute them to any location in the home using the single existing cabling and each receiver can act independently of each other. There is a savings in time and the installer does not have multiple devices to connect or buy in order to handle the telephone signal separately.

With the system and method of the present invention, the installer simply connects the satellite signal and the off-air/ cable to multiswitch just as he currently does with existing multi-switches. Next, instead of wasting valuable time trying to figure out which "telephone line connection fix" is best for the particular job at hand, the installer simply connects a phone signal to the new multiswitch or triplexer. This is a great savings in cost over the current solution not only in reducing the cost of associated equipment the installer must purchase and the labor that is involved, but it also reduces time lost on a job due to down time as the installer tries to figure out which "fix" is best. Also it takes all of the guesswork out any particular job for a less experienced installer. It is expected that the installer will find a phone line located near the multiswitch or one of the triplexers to which to connect. After he has located a phone signal, the installer simply plugs it into the multiswitch or triplexer that is near-by. The system of the present invention does the rest of the work including delivering all three needed signals to all locations in a home across existing coax cable or wire.

To an end user, the multiswitch and triplexer of the present invention offers a major cost savings in the labor required for installation, reduces the cost of associated equipment needed to connect a telephone service to a satellite receiver, and ensures an esthetically pleasing system installation. To the satellite provider it helps to ensure that each installation has a phone connected to the satellite receiver so that it can verify the location of each receiver, download all pertinent charges from the many different

pay-per-view options which also helps to increase the satellite provider's revenues because all installations will now have a phone signal properly connected resulting in an increase in orders due to the ease of the ordering process, help to end theft or pirating of the satellite signal, and helps to lower installation costs when compared to current satellite jobs which is most desirable in light of the current "free" installation programs satellite providers are offering.

The system of the present invention, which combines three needed signals and transmits the combined signal over a coax that already exists in a home or structure, is a needed accomplishment. The system does not simply combine the signals. It manages the transmission of radio frequency and telephony signals and processes programming and telephony requests from multiple receivers to which it communicates. One embodiment of the present invention includes a triplexer. The receiver controls the multiswitch using its own system protocol that it transmits to the multiswitch via a coaxial cable connection through the triplexer to the multiswitch output RF connector for channel selection and telephone connection. The triplexer modifies the protocol of the receiver and creates a unique protocol to which the multiswitch will respond. The duties of a multiswitch include analyzing the protocol and transmitting requested signals to each receiver, which may differ based upon the selection in each receiver. By way of example, satellite channels have pre-assigned signals that are transmitted by the satellite provider. Typical receiver channel selection protocol includes using a control signal varying between a 13 volts DC or 18 volts DC level with or without the presence of a 22 kHz signal. The triplexer analyzes the receiver channel selection request as well as any request for a dial tone connection. The multiswitch must process each request from a receiver then send the proper channel and/or telephony connection to that receiver. The microcontroller operable with the multiswitch communicates with the controller in each triplexer through the coax in order to determine if a dial tone is present at any of the triplexers or at the multiswitch in order to process channel and telephony path connections. Current system protocol signals, 13 and 18 volt plus the 22 kHz signal, make it difficult to transmit the phone signal simultaneously. With the present invention, between the multiswitch and the satellite receiver, the 18 and 13-volt

signals and the 22kHz signal are changed to a new and different format to avoid interference of these signal voltages with the telephone signal. One embodiment of the present invention as will be later described in further detail includes a triplexer. The request is then processed and transmitted back to the triplexer. Before it can be transmitted, the requested channel must be changed to the new format. When the triplexer receives the requested channel, it changes it back to the original signal for recognition by the receiver.

While the multi-switch is processing the satellite signal, off-air antenna and phone signals are being transmitted across the coax cable or wire. Off-air/cable, phone and satellite signals must be able to operate simultaneously and not interfere with each respective signal. This allows the receiver to do multiple tasks at the same time. An example of this is a user of a satellite watching a satellite channel and at the same time receiving an incoming call. The multi-switch must now pass the phone signal to the receiver where it is recognized. Then it processes the phone signal so that a caller I.D. may be shown on the users screen where the viewer is watching a satellite channel.

Another example is a simple activation of a satellite receiver or receivers by an installer. When an installer has finished connecting a satellite, phone and off-air/cable signals, he is at a stage where they must activate the satellite receiver with the satellite provider. With the TV and the satellite on, the installer contacts the provider by phone. The satellite provider must at the time of the call be able to interact with the receiver or receivers. If the phone signal is not connected to the receiver then the provider will not activate the receiver. Therefore the multi-switch must be able to send all needed signals simultaneously to any satellite receiver that is to be activated.

### **Brief Description of the Drawings**

Preferred embodiments of the present invention are herein presented as well as others that will become more apparent by referring to the following detailed description and drawings in which:

FIG. 1 is a system block diagram of one embodiment of the present invention illustrating a telephony signal insertion device operable with a multiswitch for switching satellite and cable television broadcast signals combined with telephony information for transmission over a single coaxial cable to a receiver;

5 FIG. 1A is a system block diagram of an alternate embodiment of FIG. 1 illustrating the telephony signal insertion device carried by the multiswitch having seven RF input signals and telephony information combined for a four way output to the coaxial cable operable with a receiver;

10 FIG. 2 is a block diagram illustrating an alternate embodiment of the multiswitch and triplexer of the present invention;

FIG. 2A is a block diagram of an alternate embodiment of the system of FIG. 2 in keeping with the teachings of the present invention;

FIGS. 3A and 3B are schematic block diagrams illustrating alternate embodiment of a triplexer of the present invention;

FIGS. 4 is a partial block diagram illustrating operating elements of the embodiments of FIGS. 2 and 2A;

FIG. 5 is a partial functional flow diagram illustrating a baseband communications system including a microcontroller operable with the multiswitch and triplexer of FIGS. 2 and 2A;

20 FIG. 6 is a schematic block diagram illustrating one implementation of the system of FIG. 5; and

FIG. 7 is a functional flow diagram illustrating an alternate embodiment of a controller of FIG. 5.

### 25 Detailed Description of Preferred Embodiments

The present invention will now be described more fully with reference to the accompanying drawings in which preferred embodiments of the invention are shown and described. It is to be understood that the invention may be embodied in many different forms and should not be construed as limited to the illustrated embodiments set forth herein. Rather, the applicant provides these embodiments so that this



disclosure will be thorough and complete, and will convey the scope of the invention to those skilled in the art.

With reference initially to FIG. 1, one embodiment of the present invention as herein described comprises a system **10** for switching multiple broadcast signals **12** from satellite antennas **14** and terrestrial antennas or cable **16** for transmission through a single coaxial cable **18** to a television receiver **20** while managing use of the broadcast signals through telephony signal **22** insertion. The system **10** incorporates passage of a telephony signal **22** and an RF signal **24** on the single coax **18** between a multiswitch **26** and a triplexer **28**. By way of example for one embodiment of the present invention, a telephony interface **30** provides an RJ-11 connector port **32** on an eight input (D8) **34** interface for connection to the multiswitch **26** through a data access arrangement (DAA) device **36** which brings the outside phone line signal **22** into operation with the multiswitch **26**. As will be described later in further detail, one embodiment of the triplexer **28** has a similar DAA device for connecting to an outside line interface. The triplexer **28** also includes an RJ-11 connection **40** to a subscriber line interface circuit (SLIC) to interface to the receiver to provide a dial tone (DT) and telephony information, as will be later described.

The multiswitch **26** and telephony interface **30** route telephony information to the receiver **20** either using a triplexer as a direct connection to the wall (the single coax **18** running through the building, by way of example) or by going from one triplexer **28** through the multiswitch **26** to another triplexer to provide the telephony information such as a dial tone. This functionality is illustrated with reference again to FIG. 1, wherein a separate box is used to carry the telephony interface **30** for installer connection to a standard multiswitch for providing the telephony signal injection as will be described later in this section. Alternatively, one embodiment of the invention includes the system **10** of FIG. 1A incorporating the telephony interface **30** within the multiswitch **26** for providing the telephony information as above described. It is to be understood that a multiswitch may have multiple input ports **42** and output ports **44** as desired, and those illustrated with reference to the attached drawings are provided by way of example.

With reference now to FIG. 2, one preferred embodiment of the system **10** includes input ports **42** providing six satellite port connections **46** and a cable T.V. port feed connection **48** which as herein provided by way of example are routed through output ports **44** to as many as eight receivers **20**. Cascaded antenna outputs **50** are provided after initial antenna signal processing within the multiswitch **26** for providing a feed to other multiswitch antenna ports thus allowing a cascading of the antenna ports to feed multiple receivers. As earlier described with reference to FIGS. 1 and 2, the multiswitch **26** interfaces to the triplexer **28**. Alternate triplexer embodiments will include a "high end" triplexer **28h** or a "low end" triplexer **28l** as illustrated with reference to the system of FIG. 2B and to the triplexer diagrams of FIGS. 3A and 3B. The "high end" triplexer **28h**, so named for its added features over a "low end" triplexer **28l**, has a SLIC interface device **52** and a DAA interface device **54**. The SLIC **52** is a subscriber line interface that allows connection to the receiver **20** and the DAA interface **54** allows connection to an outside wall line connection **54**. The function of DAA device **36** is to detect a ring or connection signal to the outside ring connection and the SLIC device **52** is used to regenerate the ring and connect to the receiver **20** for providing connectivity through the multiswitch **26**.

The block diagram of FIG. 2A illustrates, by way of example, a low end system **10l** having the multiswitch using either a low **28l** or high **28h** end triplexer **28**. Low end and high end as herein described refer to the cost of the equipment and allow for optional uses as desired by the installer or customer. By way of example, for the low end system **10l** of FIG. 2a, four satellite inputs ports **42** are provided as well as an antenna cable connection **48**. The cascading outputs **50** may or may not be included depending on the intended use of the system **10l**. The system **10** optionally includes cable TV upstream components **56** to allow a cable modem **58** in place of a receiver **58** and triplexer **28** to provide cable modem access from the cable connection **48** through the multiswitch **26**. By way of further example and with reference again to FIG. 2A, the low end embodiment of the system **10l** as herein described has only a downstream connection **60** for providing cable TV or off air antenna programming coupled with the satellite input feeds.

With continued reference to FIGS. 2 and 2A, the block diagram signal input flow starts at the top portion where either a vertical **42v** or a horizontal **42h** polarization is provided by the satellite signal antenna **14**. The system provides 13 volt and 18 volt biasing **62**, respectively. The 13 volt signal is referred to as vertical or as having right hand polarization, and the 18 volt signal as horizontal or as having a left hand polarization. These biases are fixed onto each of the respective ports. Signal gain and filtering **64** provide a desired 950 to 1450 MHz signal passage from the satellite antenna ports **46**. Distributed couplers **66** provide uniform feeds to each of the single pole multi-throw switches **68** which will connect to each antenna port and satellite antenna port and allow a master microcontroller **70** to select the needed programming feed for routing to a particular receiver **20**. The switches **68** are controlled by the master microcontroller **70** described in further detail later in this section. In the embodiment herein described, the microcontroller **70** is carried within the multiswitch housing, as illustrated with reference to FIG. 4, but it is to be understood that the microcontroller may be external without departing from the teachings of the present invention. Returning to FIGS. 2 and 2A, after the switch **68**, fixed gain and RF slope equalization components **72** compensate for higher frequency attenuation due to cable losses. After the slope equalizer, a coupler **74** is provided for coupling the cable T.V. line **76** with the satellite feed **78** so that a single feed, the single coax **18** to each triplexer, can be used for connecting to the appropriate receiver **20**. Variable gain **80** is provided at the output for adjusting the signal level for the satellite as well as terrestrial signals. The telephony signal is diplexed **82** with the RF signal for transmission over the common and single coax **18** to the triplexer **28**. Once the signal leaves the multiswitch **26**, it is carried by the coax to the triplexer **28**.

As illustrated with reference again to FIGS. 2 and 2A, the triplexer **28** functions to split the satellite portion of the frequency band and the cable portion of the frequency band as well as the telephony portion of the band that is being transported across the coaxial cable **18**. As illustrated with reference again to FIGS. 3A and 3B, within the telephony portion of the triplexer **28** is a microcontroller **84** that provides a control signal used between the triplexer and the master microcontroller **70** of the multiswitch **26** to

control the RF and telephony switching between a triplexer and a multiswitch and a triplexer multiswitch triplexer path.

By way of example and with reference now to FIG. 4, consider one multiswitch that provides for standard satellite functionality having six feed connections **46** and a cable T.V. connection **48** as earlier described with reference to FIG. 2, as well as providing the cascading **50** from one multiswitch to another multiswitch. The cascading eliminates the need to split the satellite signals at the antenna using additional electronics and opening oneself to potential signal loss problems. As earlier described, the triplexer **28** provides a filter for separating the satellite portion of the band from the 950 to 1450 MHz to the receiver satellite input from the coax **18** and also splits out the cable T.V. portion of the band, which when including the upstream, goes from 5 MHz to 860 MHz. The other portion of the band is coupled through two resistors and passes the telephony from 300 Hz to 3400 Hz, and the controller signal of approximately 57 kilohertz out.

Consider detail with respect to the telephony portion of the system with reference again to FIGS. 4 and 3A in which a telephony interface to the "outside world" is through the RJ-11 connectors. One RJ-11 connector **88** on the triplexer **28** is connected to the SLIC device **52** that provides an interface for generating a ringing signal and connects directly to a satellite receiver **20**. The second RJ-11 connector **90** connects to the DAA device **54** that detects a ring signal and is optionally connected to the outside telephone line **54** to the central office. The SLIC device **52** generally has three control lines **92** that control the state of operation and a detect line **94**. The control lines **92** are generally referred to as C1, C2, and C3. The detect line **94** is used when the satellite receiver essentially picks up the line to make a telephone call, at which point the signal on the detect line of the SCIC goes low. The three control lines **92** on the SLIC device **52** can place the SLIC device in ringing mode, active mode, on hook transmission (OHT) mode, for passing the CID information, and standby mode. With continued reference to FIG. 4, the DAA device **36** has three control lines **96** to take the DAA off-hook, to allow the DAA to pass caller ID information, and for the ring detect. Both the DAA and the SLIC devices have audio in **98** and audio out **99** lines.

As above described, the system **10** of the present invention, described by the embodiments herein presented by way of example, permits a merging of all three desired signals, including the satellite signal, the off-air antenna or cable television, and the telephony signal. Further, these signals can be distributed to multiple locations so that the satellite receivers **20** can work independently of one another. As a result, an installer can simply connect a satellite signal, an off-air antenna, and a telephone signal, all at one easy location in a single multiswitch **26**. By way of further example, and with reference to FIGS. 2 and 2A, the installer also has the option of connecting the telephony signal at the triplexer. The system of the present invention permits a merging of all three desired signals, including a satellite signal, off-air antenna or cable television, and a telephone signal. Further, these signals can be distributed to multiple locations so that the satellite receivers can work independently of one another. As a result, an installer can simply connect a satellite signal, an off-air antenna, and a telephone signal, all at one easy location in a single multiswitch device. The installer also has the option of connecting the telephone signal at the triplexer instead for providing distribution of dial tone to other triplexers and receivers through the multiswitch in situations where a telephone signal is not present at the multiswitch location. The installer connects the existing cabling to the outputs of the multiswitch device and delivers all three signals over one coax to each receiver location. This triplexer separates out the multiplexed signals so that the installer can connect them to their respective connections on the receiver. This is an easy solution for the installer or the homeowner. A single system that can merge all three signals and distribute them to any location in the home using the single existing cabling and each receiver can act independently of each other. There is a savings in time and the installer does not have multiple devices to connect **28h** instead for providing distribution of dial tone to other triplexers and receivers through the multiswitch **26** in situations where a telephone signal is not present at the multiswitch location. The installer connects the existing cabling to the outputs of the multiswitch **26** and delivers all three signals over the one coax **18** to each receiver location. The triplexer **28h** separates out the multiplexed signals so that the installer can connect them to their respective connections on the

receiver. This is an easy solution for the installer or the homeowner. A single system that can merge all three signals and distribute them to any location in the home using the single existing cabling and each receiver can act independently of each other.

By way of example, when a call comes in, it comes into a DAA device within the system. When the call comes into the DAA, it comes in as a ringing signal. That ringing signal on the DAA device has to be duplicated on all of the SLIC devices on the system. Once the first ring is passed, then the audio from that DAA device has to be patched into all of the audios on the SLIC devices within the system so that the caller ID information can be passed from the DAA device through the SLIC devices to all the satellite receivers. When a second ring comes in again, it comes into the DAA device, but has to be duplicated to all the SLIC devices and so on and so on until the call eventually stops. In an example where the satellite receiver dials out, the system actually has to find the active line connected to one of the DAA devices in the system. It senses that by looking for a DC voltage on any one of the DAA ports which indicates an active line. When the satellite receiver tries to call out, the SLIC device detect control line goes low to signify that event. The microprocessors **70, 84** automatically patch the audio in and audio out from the SLIC device to the audio in and audio out of the particular DAA device that has a DC voltage on it and then takes the DAA device into the off mode which allows the satellite receiver to get a dial tone. Once the satellite receiver gets the dial tone it proceeds with dialing out.

With reference now to FIG. 5, a baseband communication system **100** includes the controllers **70, 84** for controlling the telephony signal **22**. The baseband communication system **100** has bidirectional audio and bidirectional digital communication signals transmitted over the single conductor **19** that is the center conductor of the coax cable **18** that runs from the multiswitch **26** to the triplexer **28**. The audio signaling **102** is bidirectional in that it is going in both directions at the same time over the coax **18**. The digital signaling **104** has bidirectional capability but since in this device the master microcontroller /processor **70** in the multiswitch **26** poles the triplexers **28**, the digital communication ends up being a half duplex. Operation of the system **10** is controlled through this hybrid device **100**. The audio in signal **102** is

biased up **103** on a DC level and then the digital in signal **104** is either set to a 0 or 5 volts. The digital signal either multiplies **105** the audio by a plus one or a minus one and then it is delivered to the center conductor **19** of the coax cable **18** after going through a 600 ohm resistor **106**, **107**. Part of the hybrid device **100** includes a  
5 subtractor **108** that operates to subtract the local outgoing signal so that only the received signal is detected at the output of the subtractor. The subtractor **108** operates with a comparator **110** to recover a returned digital signal **112** and includes an absolute value circuit **114** to recover a returned audio signal **116**.

One embodiment of the hybrid device **100** is further detailed with reference to  
10 FIG. 6 where a working implementation includes two hybrid devices **100**, **101**. One hybrid on each side of the coax cable **18** which allows simultaneous transmission of two audio signals bidirectional and two digital signals of bidirectional to be recovered at both ends without interference. The following describes one embodiment of the present invention including the hybrid operating as a voltage multiplexer, which allows analog, the telephony audio, and digital, the controlling signals, to be transmitted  
simultaneously over the single wire **19** and recovered at a far end. Traditional communication methods use either time domain multiplexing, or frequency domain multiplexing to enable multiple signals to share a single medium. The technique of the  
present invention herein described employs a voltage multiplexing in which two, or  
20 more, baseband signals, that occupy the same frequency spectrum, can be simultaneously transmitted and independently received.

With reference again to the FIG. 6, Audio\_1\_IN and Digital\_1\_IN originate on the left side and are received on the right as Audio\_1\_OUT and Digital\_1\_OUT. Simultaneously Audio\_2\_IN and Digital\_2\_IN are being transmitted from the opposite  
25 direction and are being detected at Audio\_2\_OUT and Digital\_2\_OUT. The Audio\_1\_IN (Pt. A) is raised to a dc level (in this example) of +2.5 volts (Pt. B). The highs and lows of the Digital\_1\_IN waveform determined if the analog voltage is inverted at Pt. C. In this example, a high causes the offset analog voltage to remain non-inverted while a low causes the offset analog voltage to invert (Pt. C). The  
30 combined signal at Pt. C is received at the far end (Pt. K) without interference with the

Audio\_2\_IN and Digital\_2\_IN signals that are coming from the far end. This simultaneous bidirectional communication is possible because the receiving amplifier at each end samples and subtracts out the signal from its own transmitter. Therefore at Pt. K, the only signal that exists is the signal present at Pt. C. Because the signal at Pt. K goes through a full wave rectification, the digital information is completely removed with only the analog (Audio\_1\_IN) remaining (Pt. M). A comparator also acts on the signal at Pt. K to remove the analog audio and recover the Digital\_1\_IN at Pt. L.

Although not explicitly shown, the Audio\_1\_IN can be a previously encoded mixture of digital and analog, in which a second level of encoding and decoding would allow two baseband digital signals to be transmitted along with the baseband audio and all three recovered without interference. Multiple levels of encoding and decoding could be used to transmit baseband analog and several baseband digital signals, limited only by the system signal-to-noise performance of real devices.

Unlike that suggested in the art, the triplexer detects the thirteen or eighteen volt signals and determines whether or not the 22 kilohertz signal is present and relays that information to the master microcontroller in the multiswitch. As a result, microcontroller communication provides the telephony information transfer between the multiswitch and the receiver via the triplexer rather than passing the telephony audio voltage signal over the coax.

By way of further supporting description, the SLIC (Subscriber Line Interface Circuit) is the chip that interfaces with the satellite receiver (or telephone). A SLIC interface can generate a ring signal but cannot detect a ring signal. Functionally, the SLIC is the interface your telephone sees at the phone company. The SLIC has audio in and audio out lines and has a DET digital output that goes LOW when the satellite receiver (or a telephone) goes off-hook to dial out. The SLIC has three digital control inputs that are used to set the SLIC in Standby, Ringing, Active, or Caller ID Transmission (OHT) mode depending on circumstances. The DAA (Data Access Arrangement) is a module that detects a ringing signal, but does not generate one. The DAA is the device in your home that typically makes the connection of the telephone to the telephone company switch. Consider the DAA to be a phone. The DAA has audio



in, and audio out lines, has a ring output line that pulses when a ring signal arrives, and has customer identification (CID) information input control line that is forced low to pass Caller ID information. The DAA further has an "on hook" (OH) input control line that is forced low to answer the incoming phone call.

5       The hybrid device has a digital input, digital output, analog input, and analog output, and can multiplex bidirectional baseband analog and digital signals onto a single center conductor of the coax cable joining the triplexer and the multiswitch. The analog is 300-3400 Hz. The digital can be any frequency from almost dc to over 100 KHz. 56 Kbaud (28 KHz.) is used in the embodiments herein described by way of example.

10       Voltage division multiplexing is used to keep the analog and digital from interfering with each other. The RF signals range from 5 MHz to 1450 MHz and thus is sufficiently removed from the frequency range of both the telephony analog and digital signals so as to avoid interference. Voltage division multiplexing permits telephony information to be added to the multiswitch inexpensively. The digital transmission in the system includes a burst of data lasting a short period of time. This burst of data generally only occurs every tenth of a second and can interfere with the analog information for 400 microseconds. With respect to frequency domain, the analog signal is transmitted baseband (bidirectional). The digital, which comes along every tenth of a second, is transmitted baseband, for its duration of 400 microseconds. During that time, the digital data is actually used to up-convert the analog out of the way to a spread spectrum frequency until the duration of the digital burst is passed. The analog signal is completely recovered with non-linear processing (the absolute value circuit) so that there is no lose in the analog signal during that time. A switch matrix in the multiswitch allows any analog input/output combination from any hybrid to be connected to any other analog input/output to other hybrid(s). The switch matrix in the triplexer allows the analog input/output from either the DAA of that triplexer or the SLIC of that triplexer to be routed to the hybrid within that triplexer for transmission over the coax cable to the corresponding hybrid in the multiswitch. The multiswitch can then reroute the analog connection via another hybrid to either the SLIC or the DAA in any other triplexer, or to the DAA within the multiswitch, as may be the case.

An alternative embodiment to the hybrid device **100** of FIG. 5 is illustrated with reference to FIG. 7 and employs an encoding of both the audio and digital on the same center conductor of the coax cable. Square waves used by the microcontrollers to talk to each other are combined with digital pulses to encode the square wave into a 32 kilohertz carrier and summed that into the audio signal. As a further modification, instead of using the 600 Ohm resistor to couple the signal to the coax cable, a small audio transformer **118** is employed, as illustrated with reference to FIG. 7A. The transformer **118** allows for a coupling of the audio and the digital signals, but also allows the uninhibited passing of the 18 volts and the 22 kilohertz that are needed for control signals for the multiswitch.

Consider the following various situations that may occur.

Case 1. Incoming call (Recall that the SLIC connects to satellite receivers, or telephones; the DAA connects to the phone company.) A 2 second ring signal comes into a DAA somewhere in the system. That 2 second ring signal is regenerated by every SLIC in the system. Immediately after the first ring (which last 2 seconds) the DAA is placed in CID mode. All the SLIC devices are placed in OHT mode for 4 seconds, and the switch matrix sets up a parallel path between the DAA to all the SLIC devices in the system. This passes the incoming caller ID signal to all the satellite receivers (or telephones) in the system. The second ring signal is detected by the DAA and regenerated by all the SLIC devices in the system. The SLIC devices are put in standby mode between all subsequent rings. The third ring signal is detected by the DAA and regenerated by all the SLIC devices in the system, and so on. If at any point, a satellite receiver (telephone) were to answer to call, the detect line on the corresponding SLIC would go low, and the OH line of the corresponding DAA would be pulled low by the system microcontroller, and the switch matrix would set up an analog path between that SLIC and that DAA. When the SLIC DET line goes high, the system knows that the call is terminated and pulls the OH line high on the appropriate DAA and the switch matrix disconnects the analog path.

Case 2. Outgoing call (SLIC devices connect to satellite receivers, or telephones; DAA devices connect to the phone company.) The satellite receiver (or telephone) goes off-

hook to dial out. The DET line for the corresponding SLIC goes low. The system looks for an active line connected to any DAA in the system. It determines this by the presence of a DC voltage on the line. The system then pulls the OH line low for that DAA and sets up the switch matrix to connect the audio in/out of that DAA to the audio in/out of the corresponding SLIC. The satellite receiver (or telephone) then gets a dial tone and can dial out. (Normally a satellite receiver would wait up to 5 seconds for dial tone before giving up.) When the SLIC DET line goes high, the system knows that the call is terminated and pulls the OH line high on the appropriate DAA and the switch matrix disconnects the analog link.

Many modifications and other embodiments of the invention will come to the mind of one skilled in the art having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is to be understood that the invention is not to be limited to the specific embodiments disclosed, and that modifications and alternate embodiments are intended to be included within the scope of the appended claims.